



**product description:**

designed for distribution system with voltage 400 V and with maximum current 16 A  
 intended for devices of Classic and Swing - ABB series  
 suitable for devices with great mounting depth  
 on the sides of the box are marked inlets for the trunkings  
 to install on materials with fire classes E or F, use insulating pad

**material:** PVC

color: white / imitation pink birch / imitation dark oak / light brown

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-D

weight: 46 g

meets the requirements: EN 60 670-1

storage: ČSN 64 0090

LK 80X28R/1\_HB - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - white

LK 80X28R/1\_I1 - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - imitation pink birch

LK 80X28R/1\_I2 - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - imitation dark oak

LK 80X28R/1\_SD - 10 pcs of boxes including device screws packed in foil; 120 pcs of boxes in carton; color - light brown

**accessories:**

- screwless terminal plates TYP015, TYP016, TYP017, TYP018
- cover VLK 80/R
- extending frame NR 80/R
- thermo-isolating pad PI 80R
- terminal plate S-66

